




TOPP ACK4 RWA

Protivpožarni pogon za automatizaciju kip prozora, krovnih prozora i kupola



Opis proizvoda

ACK 4 RWA je pogon sa lancem za automatizaciju prozora, namenjen za specijalne uslove protivpožarne zaštite i odimljavanja. Njegovo specijalno vatrostalno kućište od livenog aluminijuma presvučeno je epoksi prahom, a hod je podesiv do 400 mm u razmacima od 50 mm. Uređaj spada u klasu zaštite IP55, a konstruisan je i proizveden u skladu sa standardima CE sertifikata i standardom EN12101-2 za odimljavanje.

MODEL	ACK4
NAPON NAPAJANJA	24V
SNAGA POTISKIVANJA	300N
SNAGA PRIVLAČENJA	300N
HOD	100 - 150 - 200 - 250 - 300 - 350 - 400mm
STRUJA	1,35A
BRZINA PRAZNOG HODA	17 min/s
DUPLA IZOLACIJA	Da
VRSTA I TRAJANJE RADA	S2 3min
RADNA TEMPERATURA	-5°C +55°C
KLASA ZAŠTITE	IP55
MOGUĆNOST PARALELNOG VEZIVANJA	Da
SINHRONIZOVAN RAD VIŠE MOTORA NA ISTOM PROZORU	Sa S verzijom motora
KONTROLA POZICIJE LANCA	Da
KRAJNJA POZICIJA OTVARANJA	Enkoder
ZVUČNI SIGNAL UPOZORENJA OD GREŠAKA U INSTALACIJI	Da
DIMENZIJE	288,5x83x47,8 mm



Tehnički nacrt

